

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/2095/162/09/19/2662

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: **Kupfer Hermanos S.A.**

Libertad #54,8350635, SANTIAGO

CHILE

Description

protective glove against mechanical risks PPE Type:

Product reference: GRIP Nitrile 3/4

Article code: N3501-B

13 GAUGE Blue Polyester Liner Black Nitrile Foam 3/4 Coated Glove description:

Available sizes : 7/S 8/M 9/L 10/XL 11/XXL

Pictures:



GRIP Nitrile 3/4 N3501-B

EN388:2016

Talla 9/L

4121X Hecho en China

Libertad#54, 8350635, Santiago, Chile Lot:XXXXXX

XX/XX (Month/Year)

Reference standard:

Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

4121X

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from SEPTEMBER 2019

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by Maxence DREVET **Project Certification Manager**

End of validity date: 06 September 2024

Date of first issue: 06 September 2019



Original CTC

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

www.ctcgroupe.com

cemarking@ctcgroupe.com

Kupfer Hermanos S.A.

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : GRIP Nitrile 3/4

Article code : N3501-B

Technical file index : 01

Last update : SEPTEMBER 2019

IDENTIFICATION

Reference of the product : : GRIP Nitrile 3/4

Article code: : N3501-B

Basic Model

Technical file index: : 01

Last update : SEPTEMBER 2019

Manufacturer:

Kupfer Hermanos S.A. Libertad #54,8350635, SANTIAGO CHILE

tel: 56 2 2351 5154

fax:

Factory:

SHANDONG XINGYU GLOVES CO.,LTD

MIDDLE YAOQIAN ROAD CHAOYANG DISTRICT GAOMI CITY SHANDONG PROVINCE

CHINA

tel: 0086-536-2587338 fax: 0086-536-2586328

GLOVE DESCRIPTION

General glove description:

13 GAUGE Blue Polyester Liner Black Nitrile Foam 3/4 Coated type of coating finish: foam

Visual description (picture back and palm sides):



Field of use

construction industry, hardware industry

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
			Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	\ \	✓ Standard	
			✓ Instruction for use	
			✓ Marking	
§1.4	Manufacturer's instructions and information is available	>	Standard	
			✓ Instruction for use	
			Marking	
	PPE which may be caught up during use	>	Standard	
§2.5			✓ Instruction for use	
			Marking	
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	>	✓ Standard	
			✓ Instruction for use	
			✓ Marking	
§3.3	The PPE is intended to protect against mechanical injuries	7	✓ Standard	
			✓ Instruction for use	
			✓ Marking	

Available sizes:

Minimum length of glove (mm)	Sizes
230	7/S
240	8/M
250	9/L
260	10/XL
270	11/XXL

Glove constitution:

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		black	nitrile	470g/m2		1.31 - 1.38 mm (complex with the shell)
		blue	polyester	180g/m2	13gauges/ inch	
Back	3/4 coating	black	nitrile	470g/m2		1.31 - 1.38 mm (complex with the shell)
		blue	polyester	180g/m2	13gauges/ inch	
Cuff		blue	polyester/elastic	305g/m2	13gauges/ inch	
Binding		white	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425. This glove is designed against mechanical risks. It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity: 5 Size: conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388: 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

TEST REPORTS

Laboratory	CTC	Other
	S190100162_1 S190100163_1 S160605952_1	
EN 388	S190100162_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer:

Logo (€

Glove's reference: GRIP Nitrile 3/4

Article Code: N3501-B

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram Address of Manufacturer:

Date of Manufacture (month/year) and/or Serial number:

Marking example :



GRIP Nitrile 3/4 N3501-B

EN388:2016



Talla 9/L (€



Libertad#54, 8350635, Santiago, Chile

Lot:XXXXXX

XX/XX (Month/Year)

Method of marking on the glove :

printed on the back

Packaging:

12 pairs/PE bag, 144 pairs/carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available with product.

MEANS OF CONTROL

According to ISO 9001, random inspect abrasion for every batch



INSTRUCTION FOR USE

GRIP Nitrile 3/4

N3501-B

121X Hecho en China

Talla 9/L

EN388:2016

Kupfer Hermanos S.A.

Libertad #54,8350635, SANTIAGO

Libertad#54, 8350635, Santiago, Chile //ATO)

CHILE

Glove reference: GRIP Nitrile 3/4 XX/XX (Month/Year)

Article code: N3501-B

User notice index: 01

Last update: SEPTEMBER 2019

Available sizes: 7/S 8/M 9/L 10/XL 11/XXL

Glove description :

13 GAUGE Blue Polyester Liner Black Nitrile Foam 3/4 Coated

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards:

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :

__Application_:

Mechanical hazard - EN 388 : 2016



Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	Х	(A to F)
Impact Protection		
		-

[«] X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Protection limit:

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available with product.