

RED LINE Wheeled Extinguisher Models 150-C, 350-C

Features

- Listed by Underwriters Laboratories, Inc./Underwriters Laboratories of Canada (UL/ULC)
- Factory Mutual (FM) and USCG approved
- Three ANSUL® dry chemical suppressing agents available: PLUS-FIFTY C, FORAY or Purple-K
- MET-L-KYL dry chemical unit is available for hazards with Class B metal-organic compounds (pyrophoric liquids)
- Two dry powder (MET-L-X and LITH-X) units are available for Class D hazards
- Easy pressurization by turning the nitrogen cylinder hand valve
- Simple operation provided by discharge nozzle with two-position ball valve
- Aluminum nozzle barrel provides a solid, round agent stream
- Standard fill cap indicates when unit is pressurized
- Stock models available for immediate delivery (no options)
- Options: long range nozzle
quick-opening nitrogen cylinder valve
wide wheels
rubber coated tires (some models)
- Six-year limited warranty

Application

RED LINE Wheeled Fire Extinguishers are manufactured to provide protection for hazardous areas where the potential exists for large fires. They can be strategically located to provide maximum protection for a wide variety of hazards, while taking up a minimum of space, and requiring only one trained person for operation.

These extinguishers are available with up to four types of ANSUL dry chemical suppressing agents giving them the versatility to protect many types of fire hazards.

The wheeled extinguisher is completely self-contained. An attached nitrogen cylinder is the only pressure source required to completely expel the fire suppressing agent. The pressure remaining in the tank after operation is sufficient for cleaning dry chemical from the discharge hose.

Some typical applications include:

- Refineries
- Chemical plants
- Offshore platforms
- Heavy manufacturing operations
- Loading racks
- Fuel storage areas
- Airports



RED LINE CR-I-K-150-C

006501



RED LINE CR-I-K-350-C

006502

Description

Agent Tank – The extinguisher tank is manufactured of welded steel construction with two elliptical dished heads and welded circumferential seams. The tank is designed and constructed for a working pressure of 250 psi (17.2 bar). The top of the tank is fitted with a 4 in. (102 mm) ID (Inside Diameter) fill opening.

Nitrogen Cylinder and Valve – The nitrogen cylinder is mounted in a vertical position and permits easy access. Volumes are 110 ft³ (3.11 m³) for the 150-C and 220 ft³ (6.23 m³) for the 350-C.

Each cylinder is equipped with a conventional hand wheel nitrogen cylinder valve and visual pressure gauge. A quick-opening valve is available as an option. Both valves are UL/ULC listed.

RED LINE Wheeled Fire Extinguishers – Model 350-C

Model Part No. UL	CR-I-350-C 31010	CR-LR-I-350-C 417272	CR-I-A-350-C-1 435046	CR-I-K-350-C 31541	CR-LR-I-K-350-C 32972	—	—	CR-MX-350-C 417274	CR-I-ML-350-C 417276	CR-I-LX-350-C 417277
Model Part No. ULC	—	—	—	CR-I-K-350-C 435328	—	CR-LT-I-A-350-C-1 435048	CR-LT-I-K-350-C-1 435330	—	—	—
Arabic Model Part No. UL	—	—	CR-I-A-350-C-1 438632	—	—	—	—	CR-MX-350-C 435822	—	—
Spanish Model Part No. UL	—	—	CR-I-A-350-C-1 438685	CR-I-K-350-C 54381	—	—	—	—	—	—
Capacity/ Agent	350 lb (159 kg)/ PLUS-FIFTY C	350 lb (159 kg)/ PLUS-FIFTY C	300 lb (136 kg)/ FORAY	300 lb (136 kg)/ Purple-K	300 lb (136 kg)/ Purple-K	300 lb (136 kg)/ FORAY	300 lb (136 kg)/ Purple-K	350 lb (159 kg)/ MET-L-X	350 lb (159 kg)/ MET-L-KYL	315 lb (143 kg)/ LITH-X
UL/ULC Rating	240-B:C	120-B:C	40-A:240-B:C	480-B:C	160-B:C	40-A:240-B:C	480-B:C	UL Listed	Not UL Listed	Not UL Listed
Listings/ Approvals	UL, FM, USCG	UL, FM, USCG	UL, FM, USCG	UL, ULC, FM, USCG	UL, FM, USCG	ULC, FM	ULC, FM	UL, FM, USCG	N/A	N/A
Standard Hose	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)	1 in. x 50 ft (25 mm x 15 m)
Discharge Time	40 sec	55 sec	46 sec	67 sec	47 sec	46 sec	67 sec	145 sec	N/A	N/A
Effective Range	30 ft (9.1 m)	40 ft (12.2 m)	30 ft (9.1 m)	30 ft (9.1 m)	40 ft (12.2 m)	30 ft (9.1 m)	30 ft (9.1 m)	14 ft (4.3 m)	30 ft (9.1 m)	25 ft (7.6 m)
Agent Flow Rate	7.8 lb/sec (3.6 kg/sec)	7.3 lb/sec (3.3 kg/sec)	6.5 lb/sec (2.9 kg/sec)	4.9 lb/sec (2.2 kg/sec)	7.2 lb/sec (3.3 kg/sec)	6.5 lb/sec (2.9 kg/sec)	4.9 lb/sec (2.2 kg/sec)	2.1 lb/sec (1.0 kg/sec)	N/A	N/A
Charged Weight (with agent)	948 lb (430 kg)	948 lb (430 kg)	898 lb (407 kg)	898 lb (407 kg)	898 lb (414 kg)	898 lb (407 kg)	898 lb (407 kg)	948 lb (430 kg)	948 lb (430 kg)	913 lb (212 kg)
Shipping Weight	972 lb (442 kg)	972 lb (442 kg)	922 lb (419 kg)	922 lb (419 kg)	922 lb (419 kg)	922 lb (419 kg)	922 lb (419 kg)	972 lb (442 kg)	972 lb (442 kg)	937 lb (426 kg)
Dimensions:										
Height:	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)	60 in. (1524 mm)
Width:	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)	35.5 in. (902 mm)
Depth:	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)	46.5 in. (1181 mm)

ABBREVIATIONS

A FORAY Agent	LR Long Range/High-Flow	LX LITH-X
CR Corrosion-Resistant	LT Low Temperature	MX MET-L-X
I Indicator Fill Cap	WW Wide Wheel	ML MET-L-KYL
K Purple-K Agent	RT Rubber Tire	

* Stock model (without options) available for immediate delivery.

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

ANSUL, RED LINE, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.

